



SPECIFICATIONS

TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



540/65 R 38 147 D TL Traxion+ (65 Series)									
EAN		8714692259852				Section Width		540 mm	
Nominal Tyre Pressure		1,6 bar				Overall Diameter		1685 mm	
Tyre Construction		Radial				Static Loaded Radius		780 mm	
Recommended Rim Width		DW16L				Rolling Circumference		5080 mm	
Permitted Rim Width		W16L, W/DW18L				SRI		800	
						Tread Depth		47 mm	
EAN Tube		8714692331459				75% of the Tyre Volume		355 l	
Tyre Pressure (Bar)									
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00

Load Capacity per tyre (kg)									
Speed (km/h)	10L	2555	2895	3250	3595	3950	4225	4460	4735
	10H	2120	2455	2790	3080	3325	3535		
	25	2180	2530	2875	3175	3425	3645		
	30	2120	2455	2790	3080	3325	3535		
	40		2340	2660	2935	3165	3365		
	50		2245	2550	2810	3035	3230		
	65			2430	2680	2890	3075		
	70			2210	2435	2630	2800		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.