



SPECIFICATIONS

FLOTATION PRO

Engineered in the Netherlands, the advanced radial Flotation Pro supports the needs of contractors and farmers alike. Its sturdy radial construction ensures maximum performance in the most difficult field conditions.

FEATURES:

Sturdy carcass construction ensures excellent flotation properties, and makes the tyre ideal for high-speed transport.

Even surface area pressure distribution ensures minimal soil compaction and limits rutting in sensitive crop areas.

Unique tread design ensures excellent self-cleaning properties.



560/45 R 22.5 IMP 146 D TL FLOTATION PRO

EAN	8714692080845	Section Width	545 mm
Nominal Tyre Pressure	3,2 bar	Overall Diameter	1085 mm
Tyre Construction	Radial	Static Loaded Radius	490 mm
Recommended Rim Width	AG 16.00	Rolling Circumference	3295 mm
		SRI	525
		Tread Depth	17 mm
		75% of the Tyre Volume	170 l

Tyre Pressure (Bar)							
	1,20	1,60	2,00	2,40	2,80	3,20	

Load Capacity per tyre (kg)							
Speed (km/h)	10	2650	3235	3755	4305	4845	5400
	25	2325	2840	3295	3780	4255	4740
	30	2220	2715	3150	3610	4065	4530
	40	2000	2445	2835	3250	3660	4080
	50	1780	2175	2525	2895	3260	3630
	65	1470	1800	2085	2390	2695	3000
	70	1340	1635	1900	2175	2450	2730

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.