



SPECIFICATIONS

# FLOTATION PRO

Engineered in the Netherlands, the advanced radial Flotation Pro supports the needs of contractors and farmers alike. Its sturdy radial construction ensures maximum performance in the most difficult field conditions.

## FEATURES:

Sturdy carcass construction ensures excellent flotation properties, and makes the tyre ideal for high-speed transport.

Even surface area pressure distribution ensures minimal soil compaction and limits rutting in sensitive crop areas.

Unique tread design ensures excellent self-cleaning properties.



### 560/60 R 22.5 IMP 161 D TL FLOTATION PRO

<b>EAN</b>	8714692080906	<b>Section Width</b>	565 mm
<b>Nominal Tyre Pressure</b>	4,0 bar	<b>Overall Diameter</b>	1260 mm
<b>Tyre Construction</b>	Radial	<b>Static Loaded Radius</b>	560 mm
<b>Recommended Rim Width</b>	AG 16.00	<b>Rolling Circumference</b>	3850 mm
		<b>SRI</b>	600
<b>EAN Tube</b>	8714692285044	<b>Tread Depth</b>	17 mm
		<b>75% of the Tyre Volume</b>	264 l

Tyre Pressure (Bar)									
		1,20	1,60	2,00	2,40	2,80	3,20	3,60	4,00

Load Capacity per tyre (kg)									
Speed (km/h)	<b>10</b>	3425	4185	4850	5565	6265	6975	7615	8325
	<b>25</b>	3005	3670	4260	4885	5500	6125	6680	7310
	<b>30</b>	2870	3510	4070	4665	5255	5850	6385	6985
	<b>40</b>	2585	3160	3665	4205	4735	5270	5750	6290
	<b>50</b>	2300	2810	3260	3740	4210	4690	5120	5595
	<b>65</b>	1900	2325	2695	3090	3480	3875	4230	4625
	<b>70</b>	1730	2115	2455	2810	3165	3525	3850	4210

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.