



## SPECIFICATIONS

# TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

### FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



580/70 R 38 155 D TL Traxion+ (70 Series)									
EAN		8714692276972				Section Width		600 mm	
Nominal Tyre Pressure		1,6 bar				Overall Diameter		1830 mm	
Tyre Construction		Radial				Static Loaded Radius		40 mm	
Recommended Rim Width		DW18L				Rolling Circumference		5515 mm	
Permitted Rim Width		W18L				SRI		875	
						Tread Depth		55 mm	
EAN Tube		8714692331473				75% of the Tyre Volume		525 l	
Tyre Pressure (Bar)									
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00

Load Capacity per tyre (kg)									
Speed (km/h)	<b>10L</b>	3200	3630	4075	4510	4955	5305	5610	5950
	<b>10H</b>	2655	3080	3500	3920	4210	4455		
	<b>25</b>	2735	3175	3610	4040	4340	4590		
	<b>30</b>	2655	3080	3500	3920	4210	4455		
	<b>40</b>		2935	3335	3730	4010	4245		
	<b>50</b>		2815	3200	3580	3845	4070		
	<b>65</b>			3045	3410	3660	3875		
	<b>70</b>			2770	3100	3330	3525		

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.