



SPECIFICATIONS

TRAXION XXL

Engineered in the Netherlands, the Vredestein Traxion XXL is revolutionary in ensuring exceptional operator comfort. It incorporates the unique Vredestein non-parallel, overlapping tread lug design which ensures consistent ground contact for minimal vibration and maximum ride comfort.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Advanced tread design ensures excellent traction and unbeatable ride comfort.

Wide contact surface area ensures reduced soil compaction and minimal damage to sensitive crop areas.



600/65 R 28 154 D TL TraxionXXL

EAN							8714692326950							Section Width							595 mm							
Nominal Tyre Pressure							2,4 bar							Overall Diameter							1490 mm							
Tyre Construction							Radial							Static Loaded Radius							670 mm							
Recommended Rim Width							DW18L							Rolling Circumference							4405 mm							
Permitted Rim Width							W18L							SRI							700							
														Tread Depth							50 mm							
														75% of the Tyre Volume							370 l							
Tyre Pressure (Bar)																												
			0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80														

Load Capacity per tyre (kg)													
Speed (km/h)	10L	2610	2960	3320	3675	4035	4320	4555	4835	5045	5280	5510	5625
	10H	2165	2510	2855	3145	3395	3620	3835	4025	4195	4315		
	25	2230	2585	2940	3245	3500	3735	3955	4150	4325	4445		
	30	2165	2510	2855	3145	3395	3620	3835	4025	4195	4315		
	40		2390	2715	2995	3235	3450	3655	3835	3995	4105		
	50		2290	2605	2875	3100	3310	3505	3675	3830	3940		
	65			2480	2735	2955	3150	3335	3500	3650	3750		
	70			2260	2490	2690	2865	3035	3185	3320	3415		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.