



## SPECIFICATIONS

# TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

### FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



600/65 R 38 153 D TL Traxion+ (65 Series)									
EAN		8714692259869				Section Width		610 mm	
Nominal Tyre Pressure		1,6 bar				Overall Diameter		1750 mm	
Tyre Construction		Radial				Static Loaded Radius		810 mm	
Recommended Rim Width		DW18L				Rolling Circumference		5210 mm	
Permitted Rim Width		W18L, DW20B				SRI		825	
						Tread Depth		50 mm	
EAN Tube		8714692331466				75% of the Tyre Volume		465 l	
Tyre Pressure (Bar)									
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00

Load Capacity per tyre (kg)									
Speed (km/h)	<b>10L</b>	2995	3400	3815	4220	4635	4960	5235	5555
	<b>10H</b>	2485	2885	3275	3615	3900	4200		
	<b>25</b>	2560	2970	3375	3725	4020	4325		
	<b>30</b>	2485	2885	3275	3615	3900	4200		
	<b>40</b>		2745	3120	3440	3715	3995		
	<b>50</b>		2635	2990	3300	3560	3835		
	<b>65</b>			2850	3145	3390	3650		
	<b>70</b>			2595	2860	3085	3320		

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.