



SPECIFICATIONS

TRAXION XXL

Engineered in the Netherlands, the Vredestein Traxion XXL is revolutionary in ensuring exceptional operator comfort. It incorporates the unique Vredestein non-parallel, overlapping tread lug design which ensures consistent ground contact for minimal vibration and maximum ride comfort.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Advanced tread design ensures excellent traction and unbeatable ride comfort.

Wide contact surface area ensures reduced soil compaction and minimal damage to sensitive crop areas.



600/70 R 28 157 D TL TraxionXXL

EAN							8714692244629		Section Width				610 mm	
Nominal Tyre Pressure							2,4 bar		Overall Diameter				1540 mm	
Tyre Construction							Radial		Static Loaded Radius				700 mm	
Recommended Rim Width							DW20B		Rolling Circumference				4590 mm	
Permitted Rim Width							W/DW18L		SRI				725	
									Tread Depth				51 mm	
									75% of the Tyre Volume				405 l	
Tyre Pressure (Bar)														
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80	

Load Capacity per tyre (kg)													
Speed (km/h)	10L	2945	3340	3750	4150	4560	4885	5165	5475	5705	5900	6140	6190
	10H	2445	2835	3225	3605	3875	4080	4330	4515	4675	4745		
	25	2515	2920	3320	3715	3990	4205	4460	4650	4820	4890		
	30	2445	2835	3225	3605	3875	4080	4330	4515	4675	4745		
	40		2700	3070	3435	3690	3885	4120	4300	4450	4515		
	50		2590	2945	3295	3535	3730	3950	4120	4270	4330		
	65			2805	3135	3370	3550	3765	3925	4065	4125		
	70			2550	2855	3065	3230	3425	3575	3700	3755		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.