



SPECIFICATIONS

TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



620/70 R 42 166 D TL Traxion+ (70 Series)

EAN							8714692276996		Section Width				625 mm	
Nominal Tyre Pressure							2,4 bar		Overall Diameter				1930 mm	
Tyre Construction							Radial		Static Loaded Radius				880 mm	
Recommended Rim Width							DW20B		Rolling Circumference				5780 mm	
Permitted Rim Width							W18L, DW18L		SRI				925	
									Tread Depth				54 mm	
									75% of the Tyre Volume				585 l	
Tyre Pressure (Bar)														
		0.60	0.80	1.00	1.20	1.40	1.60	1.80	2.00	2.20	2.40	2.60	2.80	

Load Capacity per tyre (kg)													
Speed (km/h)	10L	3715	4215	4730	5235	5750	6160	6515	6905	7195	7445	7745	7950
	10H	3080	3575	4065	4550	4885	5175	5460	5695	5895	6095		
	25	3175	3685	4190	4690	5035	5335	5625	5870	6075	6280		
	30	3080	3575	4065	4550	4885	5175	5460	5695	5895	6095		
	40		3405	3870	4330	4655	4930	5200	5425	5615	5805		
	50		3265	3710	4155	4460	4725	4985	5200	5385	5565		
	65			3535	3955	4250	4500	4745	4950	5130	5300		
	70			3215	3600	3865	4095	4320	4505	4665	4825		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.

*Calculated Values