



SPECIFICATIONS

# TRAXION HARVEST

The Vredestein Traxion Harvest is a state-of-the-art radial harvester tyre that incorporates CHO/CFO technology in some sizes.

## FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Advanced tread design ensures excellent traction and unbeatable ride comfort.

Large contact surface area ensures reduced soil compaction and minimal rutting.

An angled lug nose deflects sharp stubble.

Angled lug ends ensure excellent lateral stability.

A straight sidewall design ensures maximised tread width and aids lateral stability.

Certain sizes incorporate CHO (Cyclic Harvest Operation) technology, making them suitable for high horsepower harvesters. These tyres are designed to meet the specific requirements of harvester manufacturers and are able to operate at lower inflation pressures under load.



## 620/75 R 26 166 A8/B TL Traxion Harvest

<b>EAN</b>	8714692311314	<b>Section Width</b>	610 mm
<b>Nominal Tyre Pressure</b>	3,2 bar	<b>Overall Diameter</b>	1585 mm
<b>Tyre Construction</b>	Radial	<b>Static Loaded Radius</b>	710 mm
<b>Recommended Rim Width</b>	DW20B	<b>Rolling Circumference</b>	4720 mm
<b>Permitted Rim Width</b>		<b>SRI</b>	750
		<b>Tread Depth</b>	46 mm
		<b>75% of the Tyre Volume</b>	457 l

Tyre Pressure (Bar)									
	0,80	1,20	1,60	2,00	2,40	2,80	3,20	3,60	4,00

Load Capacity per tyre (kg)										
Speed (km/h)	<b>10C</b>	4175	4970	5775	6675	7195	7650	8135	8720	9010
	<b>10L</b>	3685	4385	5095	5890	6350	6750	7175	7695	7950
	<b>10H</b>	2920	3465	4145	4520	4815	5275	5670		
	<b>25</b>	3030	3595	4300	4690	4995	5470	5885		
	<b>30</b>	2920	3465	4145	4520	4815	5275	5670		
	<b>40</b>			3875	4225	4500	4930	5300		
	<b>50</b>			3875	4225	4500	4930	5300		

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.