



SPECIFICATIONS

# FLOTATION PRO

Engineered in the Netherlands, the advanced radial Flotation Pro supports the needs of contractors and farmers alike. Its sturdy radial construction ensures maximum performance in the most difficult field conditions.

## FEATURES:

Sturdy carcass construction ensures excellent flotation properties, and makes the tyre ideal for high-speed transport.

Even surface area pressure distribution ensures minimal soil compaction and limits rutting in sensitive crop areas.

Unique tread design ensures excellent self-cleaning properties.



### 650/50 R 22.5 IMP 163 D TL FLOTATION PRO

<b>EAN</b>	8714692080920	<b>Section Width</b>	645 mm
<b>Nominal Tyre Pressure</b>	4,0 bar	<b>Overall Diameter</b>	1250 mm
<b>Tyre Construction</b>	Radial	<b>Static Loaded Radius</b>	560 mm
<b>Recommended Rim Width</b>	AG 20.00	<b>Rolling Circumference</b>	3850 mm
		<b>SRI</b>	575
		<b>Tread Depth</b>	17 mm
		<b>Tie bar height</b>	0 mm
		<b>75% of the Tyre Volume</b>	304 l

Tyre Pressure (Bar)									
		1,20	1,60	2,00	2,40	2,80	3,20	3,60	4,00

Load Capacity per tyre (kg)									
Speed (km/h)	<b>10</b>	3670	4485	5200	5960	6710	7425	8155	8775
	<b>25</b>	3220	3935	4565	5230	5890	6520	7160	7705
	<b>30</b>	3075	3760	4360	5000	5630	6230	6845	7360
	<b>40</b>	2770	3385	3930	4505	5070	5610	6165	6630
	<b>50</b>	2465	3015	3495	4005	4510	4990	5485	5900
	<b>65</b>	2040	2490	2890	3310	3730	4125	4530	4875
	<b>70</b>	1855	2265	2630	3015	3395	3755	4125	4435

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.