



SPECIFICATIONS

TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



650/65 R 38 157 D TL Traxion+ (65 Series)

EAN					8714692159992	Section Width				660 mm
Nominal Tyre Pressure					1,6 bar	Overall Diameter				1835 mm
Tyre Construction					Radial	Static Loaded Radius				840 mm
Recommended Rim Width					DW20B	Rolling Circumference				5450 mm
Permitted Rim Width					W/DW18L#	SRI				875
						Tread Depth				56 mm
EAN Tube					8714692331466	75% of the Tyre Volume				575 l
Tyre Pressure (Bar)										
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00	

Load Capacity per tyre (kg)

Speed (km/h)	10L	3385	3840	4310	4770	5240	5605	5915	6280
	10H	2810	3260	3705	4085	4410	4745		
	25	2895	3360	3815	4210	4545	4890		
	30	2810	3260	3705	4085	4410	4745		
	40		3105	3525	3890	4200	4515		
	50		2975	3380	3730	4025	4330		
	65			3220	3550	3835	4125		
	70			2930	3235	3490	3755		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.

FOR MORE INFORMATION ABOUT THIS PRODUCT, PLEASE VISIT WWW.VREDESTEINTYRES.COM.AU