



## SPECIFICATIONS

# TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

### FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Flexible sidewall construction ensures excellent impact absorption and operator comfort.

Rounded shoulders prevents damage to the turf and sensitive crop areas.



650/65 R 42 158 D TL Traxion+ (65 Series)									
EAN			8714692259876			Section Width			660 mm
Nominal Tyre Pressure			1,6 bar			Overall Diameter			1935 mm
Tyre Construction			Radial			Static Loaded Radius			890 mm
Recommended Rim Width			DW20B			Rolling Circumference			5775 mm
Permitted Rim Width			W/DW18L#			SRI			925
						Tread Depth			53 mm
						75% of the Tyre Volume			620 l
Tyre Pressure (Bar)									
		0,60	0,80	1,00	1,20	1,40	1,60	1,80	2,00

Load Capacity per tyre (kg)									
Speed (km/h)	<b>10L</b>	3550	4025	4520	5000	5490	5875	6200	6580
	<b>10H</b>	2945	3415	3885	4280	4620	4890		
	<b>25</b>	3035	3520	4000	4415	4765	5035		
	<b>30</b>	2945	3415	3885	4280	4620	4890		
	<b>40</b>		3255	3695	4075	4400	4655		
	<b>50</b>		3120	3545	3910	4220	4465		
	<b>65</b>			3375	3725	4020	4250		
	<b>70</b>			3070	3390	3655	3870		

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.