



SPECIFICATIONS

FLOTATION PRO

Engineered in the Netherlands, the advanced radial Flotation Pro supports the needs of contractors and farmers alike. Its sturdy radial construction ensures maximum performance in the most difficult field conditions.

FEATURES:

Sturdy carcass construction ensures excellent flotation properties, and makes the tyre ideal for high-speed transport.

Even surface area pressure distribution ensures minimal soil compaction and limits rutting in sensitive crop areas.

Unique tread design ensures excellent self-cleaning properties.



710/40 R 22.5 IMP 155 D TL FLOTATION PRO

EAN	8714692295546	Section Width	705 mm
Nominal Tyre Pressure	3,2 bar	Overall Diameter	1140 mm
Tyre Construction	Radial	Static Loaded Radius	520 mm
Recommended Rim Width	AG 24.00	Rolling Circumference	3520 mm
		SRI	550
		Tread Depth	17 mm
		75% of the Tyre Volume	250 l

Tyre Pressure (Bar)							
	1,20	1,60	2,00	2,40	2,80	3,20	

Load Capacity per tyre (kg)							
Speed (km/h)	10	3445	4210	4885	5600	6305	6975
	25	3025	3695	4290	4915	5535	6125
	30	2890	3535	4100	4700	5290	5850
	40	2605	3185	3690	4230	4765	5270
	50	2315	2830	3285	3765	4240	4690
	65	1915	2340	2715	3110	3505	3875
	70	1740	2130	2470	2830	3190	3525

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.