



SPECIFICATIONS

TRACTION FLOTATION+

When you want a bumper crop, the last thing you want is compacted soil to spoil it. The excellent flotation properties of Vredestein Flotation+ ensures limited soil compaction to allow excellent seed germination.

FEATURES:

Wide tread design with a large ground contact surface area ensures excellent flotation properties and minimal soil compaction.

Unique tread design ensures excellent self-cleaning properties.

Excellent height/width ratio ensures optimal stability.



710/45 - 22.5 IMP 171 A8 TL FLOTATION+

EAN						8714692220401		Section Width			730 mm		
Nominal Tyre Pressure						2,8 bar		Overall Diameter			1240 mm		
Tyre Construction						Bias		Static Loaded Radius			550 mm		
Recommended Rim Width						AG 24.00		Rolling Circumference			3700 mm		
								Tread Depth			20 mm		
EAN Tube						8714692335020							
Tyre Pressure (Bar)													
		1,00	1,25	1,50	1,75	2,00	2,25	2,50	2,75	3,50			

LLV		Load Capacity per tyre (kg)								HLV
Speed (km/h)	10	4180	4800	5420	6050	6650	7250	7850	8500	10350
	25	3560	4080	4600	5120	5640	6150	6700	7200	8800
	30	3340	3840	4320	4820	5320	5800	6300	6800	8250
	40			3860	4300	4740	5180	5620	6050	7400
	50					4260	4660	5060	5460	6650

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.