



## SPECIFICATIONS

# TRAXION XXL

Engineered in the Netherlands, the Vredestein Traxion XXL is revolutionary in ensuring exceptional operator comfort. It incorporates the unique Vredestein non-parallel, overlapping tread lug design which ensures consistent ground contact for minimal vibration and maximum ride comfort.

### FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Advanced tread design ensures excellent traction and unbeatable ride comfort.

Wide contact surface area ensures reduced soil compaction and minimal damage to sensitive crop areas.



### 710/75 R 42 175 D TL TraxionXXL

EAN							8714692244520		Section Width					735 mm	
Nominal Tyre Pressure							2,4 bar		Overall Diameter					2150 mm	
Tyre Construction							Radial		Static Loaded Radius					980 mm	
Recommended Rim Width							DW23B		Rolling Circumference					6395 mm	
Permitted Rim Width							DW25B		SRI					1025	
									Tread Depth					58 mm	
									75% of the Tyre Volume					910 l	
Tyre Pressure (Bar)															
		0.60	0.80	1.00	1.20	1.40	1.60	1.80	2.00	2.20	2.40	2.60	2.80		

<b>Load Capacity per tyre (kg)</b>													
Speed (km/h)	10C	5510	6250	7020	7765	8530	9135	9660	10240	10670	11045	11490	11730
	10L	4860	5515	6190	6855	7525	8060	8525	9035	9415	9745	10140	10350
	10H	4035	4680	5320	5955	6395	6900	7145	7455	7720	7935		
	25	4155	4825	5485	6135	6590	7110	7360	7680	7955	8175		
	30	4035	4680	5320	5955	6395	6900	7145	7455	7720	7935		
	40		4455	5065	5670	6090	6570	6805	7095	7350	7555		
	50		4275	4860	5435	5840	6300	6525	6805	7045	7245		
	65			4625	5180	5560	6000	6215	6480	6710	6900		
	70			4210	4710	5060	5460	5655	5900	6110	6280		

**E&OE.** Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.