



SPECIFICATIONS

TRAXION XXL

Engineered in the Netherlands, the Vredestein Traxion XXL is revolutionary in ensuring exceptional operator comfort. It incorporates the unique Vredestein non-parallel, overlapping tread lug design which ensures consistent ground contact for minimal vibration and maximum ride comfort.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Advanced tread design ensures excellent traction and unbeatable ride comfort.

Wide contact surface area ensures reduced soil compaction and minimal damage to sensitive crop areas.



800/65 R 32 178 A8/B TL TraxionXXL

EAN						8714692255113		Section Width				825 mm	
Nominal Tyre Pressure						3,2 bar		Overall Diameter				1840 mm	
Tyre Construction						Radial		Static Loaded Radius				845 mm	
Recommended Rim Width						DW27B		Rolling Circumference				5490 mm	
Permitted Rim Width						DW25B		SRI				875	
								Tread Depth				56 mm	
								75% of the Tyre Volume				815 l	
Tyre Pressure (Bar)													
		0,80	1,20	1,60	2,00	2,40	2,80	3,20	3,40	4,00			

Load Capacity per tyre (kg)										
Speed (km/h)	10C	5895	7000	8065	9135	9970	10710	11370	12185	12750
	10L	5200	6270	7370	8255	8795	9450	10035	10750	11250
	10H	4120	4995	5830	6245	6740	7375	8025		
	25	4275	5185	6050	6475	6995	7650	8325		
	30	4120	4995	5830	6245	6740	7375	8025		
	40		4670	5450	5835	6300	6890	7500		
	50		4670	5450	5835	6300	6890	7500		

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.