



SPECIFICATIONS

TRAXION HARVEST

The Vredestein Traxion Harvest is a state-of-the-art radial harvester tyre that incorporates CHO/CFO technology in some sizes.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Advanced tread design ensures excellent traction and unbeatable ride comfort.

Large contact surface area ensures reduced soil compaction and minimal rutting.

An angled lug nose deflects sharp stubble.

Angled lug ends ensure excellent lateral stability.

A straight sidewall design ensures maximised tread width and aids lateral stability.

Certain sizes incorporate CHO (Cyclic Harvest Operation) technology, making them suitable for high horsepower harvesters. These tyres are designed to meet the specific requirements of harvester manufacturers and are able to operate at lower inflation pressures under load.



800/70 R 38 CHO 181 D TL Traxion Harvest

EAN	8714692344916	Section Width	755 mm
Nominal Tyre Pressure	2,8 bar	Overall Diameter	2050 mm
Tyre Construction	Radial	Static Loaded Radius	920 mm
Recommended Rim Width	DW25B	Rolling Circumference	6080 mm
Permitted Rim Width	DW27B	SRI	975
		Tread Depth	57 mm
		75% of the Tyre Volume	887 l

Tyre Pressure (Bar)												
	0,80	1,00	1,20	1,40	1,60	1,80	2,00	2,20	2,40	2,60	2,80	

Load Capacity per tyre (kg)												
Speed (km/h)	10CHO	8180	8870	9705	10635	11700	12135	12655	13105	13500	14550	14850
	15 CHO	7495	8130	8900	9750	10725	11120	11605	12015	12375	13340	13615
	25	5385	5840	6390	7000	7705	7990	8335	8630	8890	9580	9775
	30	5225	5665	6200	6795	7475	7750	8085	8375	8625	9295	9490
	40	4975	5395	5905	6470	7120	7380	7700	7975	8215	8855	9035
	50	4770	5175	5660	6205	6825	7080	7385	7645	7875	8490	8665
	65		4925	5390	5910	6500	6740	7030	7280	7500	8085	8250
	70		4485	4905	5375	5915	6135	6400	6625	6825	7355	7510

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.