



SPECIFICATIONS

TRAXION CEREALL

The Vredestein Traxion Cereall is a state-of-the-art radial harvester/tractor tyre that incorporates CHO/CFO technology in some sizes.

FEATURES:

Non-parallel tread lugs ensure optimal self-cleaning ability.

Advanced tread design ensures excellent traction and unbeatable ride comfort.

Large contact surface area ensures reduced soil compaction and minimal rutting.

Certain sizes incorporate IF (Increased Flexion), and CFO (Cyclic Field Operation) technology, making them suitable for high horsepower tractors. These tyres are designed to meet the specific requirements of tractor manufacturers and are able to operate at lower inflation pressures under load.



IF 800/70 R 32 CFO TL 182 A8 Traxion Cereall

EAN					8714692292200	Section Width			815 mm
Nominal Tyre Pressure					2,4 bar	Overall Diameter			1945 mm
Tyre Construction					Radial	Static Loaded Radius			865 mm
Recommended Rim Width					DW27B	Rolling Circumference			5765 mm
Permitted Rim Width					DW30B	SRI			925
						Tread Depth			55 mm
						75% of the Tyre Volume			900 l
Tyre Pressure (Bar)									
		1,20	1,40	1,60	1,80	2,00	2,20	2,40	

Load Capacity per tyre (kg)								
Speed (km/h)	15C	9350	10245	11005	11690	12195	12625	13175
	40	6030	6610	7100	7540	7865	8145	8500
	50	5490	6015	6460	6860	7160	7410	7735

E&OE. Tyremax Pty Ltd makes no representation or warranties with respect to the accuracy or completeness of the contents of this publication and specifically disclaims any implied warranties of merchantability or fitness for any particular purpose and shall in no event be liable for any loss of profit or any other commercial damage, including but not limited to special, incidental, consequential, or other damages. Physical measurements of product may be within +/- 2% of what is stated here.

FOR MORE INFORMATION ABOUT THIS PRODUCT, PLEASE VISIT WWW.VREDESTEINTYRES.COM.AU