


# TRAXION+

Engineered in the Netherlands, the Vredestein Traxion+ is a premium combination of superb traction, optimal ride comfort and durability.

## FEATURES:



Non-parallel tread lugs ensure optimal self-cleaning ability.



Flexible sidewall construction ensures excellent impact absorption and operator comfort.



Large contact surface area ensures reduced soil compaction and minimal rutting.



Rounded shoulders prevents damage to the turf and sensitive crop areas.



Tyre Size	Pattern	Load & Speed	Type (TT/TL)	Section Width (mm)	Overall Diameter (mm)	Static Load Radius (mm)	Rolling Circumference (mm)
320/70R24	Traxion+	116 D	TL	320	1095	520	3280
360/70R24	Traxion+	122 D	TL	360	1150	545	3445
440/65R24	Traxion+	128 D	TL	440	1185	570	3600
380/70R24	Traxion+	125 D	TL	390	1190	565	3570
480/65R24	Traxion+	133 D	TL	490	1250	610	3760
420/70R24	Traxion+	130 D	TL	430	1245	595	3755
540/65R24	Traxion+	140 D	TL	540	1315	620	3960
480/70R24	Traxion+	138 D	TL	495	1315	620	3950
440/65R28	Traxion+	131 D	TL	440	1285	615	3890
380/70R28	Traxion+	127 D	TL	390	1295	620	3895
480/65R28	Traxion+	136 D	TL	490	1350	625	4020
420/70R28	Traxion+	133 D	TL	430	1350	640	4055
540/65R28	Traxion+	142 D	TL	540	1410	660	4240
480/70R28	Traxion+	140 D	TL	495	1415	655	4240
540/65R30	Traxion+	150 D	TL	540	1460	670	4400
480/70R30	Traxion+	141 D	TL	495	1475	695	4440
600/70R30	Traxion+	158 D	TL	-	-	-	-
540/65R34	Traxion+	145 D	TL	540	1580	745	4755
480/70R34	Traxion+	143 D	TL	495	1575	750	4765
520/70R34	Traxion+	148 D	TL	540	1640	770	4950
540/65R38	Traxion+	147 D	TL	540	1685	780	5080
480/70R38	Traxion+	145 D	TL	495	1680	795	5025
600/65R38	Traxion+	153 D	TL	610	1750	810	5210
520/70R38	Traxion+	150 D	TL	540	1750	815	5275
650/65R38	Traxion+	157 D	TL	660	1835	840	5450
580/70R38	Traxion+	155 D	TL	600	1830	840	5515
710/70 R38	Traxion+	171 D	TL	-	-	-	-
650/65R42	Traxion+	158 D	TL	660	1935	890	5775
620/70R42	Traxion+	166 D	TL	625	1930	880	5780
710/70 R42	Traxion+	173 D	TL	-	-	-	-

E&OE. All measurements are based on Vredestein and industry standards. Physical tyre measurements may vary slightly.